

# XIARR COB

Incassi / Recess spotlights



**W**  
8,5

**IP**  
40

**650°**  
FLUX HOMOLOGAZIONE

**E**



2006/95/CE -- 2002/95/CE -- 1907/2006/CE -- 2010/30/UE -- EN 60598-1 -- EN 60598-2-1 -- EN 62471 -- EN 62031

## Applicazione

Soffitto

Faro da incasso orientabile IP40 con 1 led da 8,5W.  
Corpo e flangia in lega di alluminio.  
Installazione a soffitto con molle o con apposita controcassa. Ottica arretrata anti-abbagliamento per un elevato comfort visivo. Sistema di movimento ultra sensibile con posizionamento istantaneo. Fornito con morsetto 2 poli per connessione.  
Unita di alimentazione compresa.

## Application




Ceiling

Recessed adjustable spotlight IP40 with 1x8.5W LED  
Aluminum alloy body and flange  
Ceiling installation with springs or outer casing provided. Withdrawn non-dazzling optic for more comfort  
Ultra-sensitive adjustable system with instant positioning. Provided with 2 pole terminal for connection  
Power supply unit included



KELVIN	CRI	LUMEN EFFETTIVI / REAL OUTPUT
2700	90	~ 745
3000	90	~ 935
4000	80	~ 950

## Xiarr Cob 8,5W



Codice/Cod: **3203**

FORMA SHAPE	FINITURA FINISH	COLORE COLOUR	OTTICHE OPTICALS
Tondo / Round	Light Grey White	4000 K 3000 K 2700 K	20° 50° 70°

250mA



EN 60598 2-2

### ACCESSORI / ACCESSORIES

30500014 Controcassa / Outer casing

ALIMENTATORE COMPRESO - INCLUDED POWER SUPPLY UNIT