



KRIZIA PLAF/S

FKRPBE4 - NEW-BEIGE

TECHNICAL DATA

Installation: Interno _ Lampada a soffitto

Source: Led integrato

Power: 60W

Power Supply: 220-240V AC _ 50/60Hz

Dimming: Dimmerabile _ taglio fase+push non incl.

Lumen: 5100lm-5300lm

Color Temperature: 3000K-4000K

Light Beam: 120° _ Diretta

CRI: >80

Lifespan: 30.000h

IP Rating: IP20

Insulation Class: I

Energy Class: F

Volume: 0,0579m3

Net Weight: 4.3 kg

Struttura in alluminio. Finitura in new beige. Diffusore in acrilico bianco opale. Sorgente luminosa led dimmerabile a taglio di fase tramite dimmer esterno+push (non inclusi). Dimmer compatibile (GDI002).

Aluminium frame. New beige finish. Opal white acrylic diffuser. Phase-cut dimmable LED light source via external dimmer+push (not included). Matching dimmer (GDI002).

Cadre en aluminium. Finition en nouveau beige. Diffuseur acrylique blanc opale. Source lumineuse LED à gradation de phase via un gradateur externe+poussoir (non inclus). Variateur compatible (GDI002).

Rahmen aus Aluminium. Ausführung in New Beige. Opalweißer Acryldiffusor. Phasenanschnitt dimmbare LED-Lichtquelle über externen Dimmer+Druck (nicht im Lieferumfang enthalten). Kompatibler Dimmer (GDI002).



KRIZIA PLAF/S

FKRPTE4 - TERRACOTTA

TECHNICAL DATA

Installation: Interno _ Lampada a soffitto

Source: Led integrato

Power: 60W

Power Supply: 220-240V AC _ 50/60Hz

Dimming: Dimmerabile _ taglio fase+push non incl.

Lumen: 5100lm-5300lm

Color Temperature: 3000K-4000K

Light Beam: 120° _ Diretta

CRI: >80

Lifespan: 30.000h

IP Rating: IP20

Insulation Class: I

Energy Class: F

Volume: 0,0579m3

Net Weight: 4.3 kg

Struttura in alluminio. Finitura in terracotta. Diffusore in acrilico bianco opale. Sorgente luminosa led dimmerabile a taglio di fase tramite dimmer esterno+push (non inclusi). Dimmer compatibile (GDI002).

Aluminium frame. Terracotta finish. Opal white acrylic diffuser. Phase-cut dimmable LED light source via external dimmer+push (not included). Matching dimmer (GDI002).

Cadre en aluminium. Finition en terre cuite. Diffuseur acrylique blanc opale. Source lumineuse LED à gradation de phase via un gradateur externe+poussoir (non inclus). Variateur compatible (GDI002).

Rahmen aus Aluminium. Ausführung in Terrakotta. Opalweißer Acryldiffusor. Phasenanschnitt dimmbare LED-Lichtquelle über externen Dimmer+Druck (nicht im Lieferumfang enthalten). Kompatibler Dimmer (GDI002).



KRIZIA PLAF/S

FKRPV4 - VERDE-SALVIA

TECHNICAL DATA

Installation: Interno _ Lampada a soffitto

Source: Led integrato

Power: 60W

Power Supply: 220-240V AC _ 50/60Hz

Dimming: Dimmerabile _ taglio fase+push non incl.

Lumen: 5100lm-5300lm

Color Temperature: 3000K-4000K

Light Beam: 120° _ Diretta

CRI: >80

Lifespan: 30.000h

IP Rating: IP20

Insulation Class: I

Energy Class: F

Volume: 0,0579m3

Net Weight: 4.3 kg

Struttura in alluminio. Finitura in verde salvia. Diffusore in acrilico bianco opale. Sorgente luminosa led dimmerabile a taglio di fase tramite dimmer esterno+push (non inclusi). Dimmer compatibile (GDI002).

Aluminium frame. Sage green finish. Opal white acrylic diffuser. Phase-cut dimmable LED light source via external dimmer+push (not included). Matching dimmer (GDI002).

Cadre en aluminium. Finition en vert sauge. Diffuseur acrylique blanc opale. Source lumineuse LED à gradation de phase via un gradateur externe+poussoir (non inclus). Variateur compatible (GDI002).

Rahmen aus Aluminium. Ausführung in Salbeigrün. Opalweißer Acryldiffusor. Phasenanschnitt dimmbare LED-Lichtquelle über externen Dimmer+Druck (nicht im Lieferumfang enthalten). Kompatibler Dimmer (GDI002).